

## No More Cracks Plaster Filler

### Description

No More Cracks™ Plaster Filler is a ready to use, fast drying, light weight filler for interior use only on plaster, plasterboard and wallboard.

### Product Information

Packaging	Size
Tub	100 grams
Tub	220 grams

### Uses

No More Cracks™ Plaster Filler is suitable for repairing holes, cracks, chips, dents and other imperfections. It has excellent adhesion on plaster and minimal shrinkage so no need to overfill.

### Features

- Ready to use
- Fast drying
- Easy to Sand
- Sandable in 30 minutes (in thin applications)
- Minimum shrinkage
- Water Clean Up
- Interior use only

### Technical Details

Property	Typical Result
Technology	Water-based
Colour	White
Density	0.48
Sand/paint time	30 minutes (less than 2mm depth)
Indicative data only, not intended for preparation of specifications	

### Surface Preparation

Ensure the surface to be filled is clean and dry with no loose or powdery material

### Directions for Use

1. Use a filling blade or scraper to firmly press the filler in and scrape off excess, this will minimise sanding.
2. For applications less than 2mm thick allow to dry 30 minutes before sanding and painting with water-based paints. Allow longer drying times for thicker applications.

3. Allow 24 hours minimum drying if painting with solvent based paints

### Tips

- For applications more than 2mm deep, or in cold or humid conditions, expect longer drying times.
- For best results apply an undercoat before your top coat of paint.
- If the filler is dry, stir with spatula and add one teaspoon of water and stir again

### Clean Up

Use water before filler sets.  
Cured product can be removed by sanding and scraping.

### Storage

Store product in cool dry place.  
Keep container closed when not in use.

### Limitations

- Do not use below 5°C
- Do not nail.
- For interior use only
- Where movement occurs, use Selleys No More Gaps
- Not recommended for plastic or metal surfaces.

### Warnings, First Aid and Shipping Information

This information can be located on the product SDS found through our website – [www.selleys.com](http://www.selleys.com)